



Product Information

Easy Sight Technology

X5-HR crawler

Protection class	IP68 up to 10 m water depth
Drive	Screw type
Equipment	Steerable
clutch	Electrically controllable
sensor	Laser,Sonar,CCTV- Real time HD Pan & Tilt Camera,IMU
Nominal pipe widths	DN 600 up to DN 2000
Elevator	No elevator
Power supply	Cable reel
Speed	Up to 25m/min
Ambient temperature range	-10 °C - 50 °C
Location transmission	Yes
Material	Brass nickel-plating stainless steel
Dimensions (L x W x H)	750*460*270mm
Weight	14.5kg



Easy Sight Technology

9-2,Wudayuan 1st Rd
Donghu High Tech Zone
Wuhan, China
Tel: +86 (27) 5988-0849
www.pipedetection.com



Product Information

Easy Sight Technology

Cable Reel

Drive	Motor-driven
Cable length	Max. 350 m
Meter counter	1
Protection class	IP63
Voltage	230 V AC / 115 V AC
Frequency	50 Hz / 60 Hz
Electrical current	2.5 A / 5 A
Winding aid	Yes
Invert mode	Yes
Interface	1 x Ethernet (RJ45); WiFi
Manual mode	Yes
Cable Pin	2
Dimensions (L x W x H)	570X395X475mm
Weight	75 kg incl.350m cable
Supported OS	Windows



Easy Sight Technology

9-2,Wudayuan 1st Rd
Donghu High Tech Zone
Wuhan, China
Tel: +86 (27) 5988-0849
www.pipedetection.com



Product Information

Easy Sight Technology

HR Sonar Probe

Protection class	IP68 up to 10 m water depth
Material	Stainless casing
Nominal pipe widths	DN 300 up to DN 3000
Elevator	No elevator
Power supply	Cable reel
Ambient temperature range	-10 °C - 50 °C
Frequency	1MHZ
Transmit pulse width	4-20us
Receive bandwidth	500KHz
Dimensions (L x W x H)	DN 70mm, Length: 485mm
Weight	2.7KG
Voltage	DC 48V



Easy Sight Technology

9-2,Wudayuan 1st Rd
Donghu High Tech Zone
Wuhan, China
Tel: +86 (27) 5988-0849
www.pipedetection.com



Product Information

Easy Sight Technology

X5H Camera

Protection class	IP68 up to 10 m water depth
Internal pressure sensor	Yes
Resolution horizontal	4 Mega pixels 2592 x 1520
Type	CMOS
Imager	1/4 " color
Ambient temperature range	-10 °C - 50 °C
Rotation range	Endless
Panning range	+/- 135°
View angle	68° (horizontal)
Optical zoom	10 x
Illumination	4 LED
Focus	Automatically and manually
Laser pointer	Yes
Sensitivity to light	0.1 Lux
Material	Aluminum
Dimensions (L x W x H)	155 x 95 x 90 mm
Weight	1.5 kg



Easy Sight Technology

9-2,Wudayuan 1st Rd
Donghu High Tech Zone
Wuhan, China
Tel: +86 (27) 5988-0849
www.pipedetection.com